




Urban Oak

## KING FLOOR 12mm LAMINATE



Urban Oak	Description	Test Standard
Country of origin	Poland	
Dimensions	1380 x 188 x 12mm	EN-13329
Pack size	1.30m <sup>2</sup>	-
Pallet quantity	60 packs	-
Weight	13.88kg	-
Construction	HDF 860kg/m <sup>3</sup>	-
Classification	Class 23/33	EN-13329
Abrasion resistance	AC5	EN-13329
Bevel	4V	-
Locking system	G5 Express Click	-
Structure	Cyncro 3D, WG, WP, CP	-
Bathroom use	No	-
Underfloor heating	Yes	-
Warranty	30 year residential	-

**Technical Specification**

Product	Description	Test Standard
Fire resistance	Cfl-s1	EN-13501-1
Impact resistance	Small ball - AC5 > 15N Big ball - AC5 > 1000mm	EN-13329
Thermal resistance	12mm: R<0.099 (m <sup>2</sup> K)/W	EN-12667
Slip resistance	DS	EN-13893
Formaldehyde emission	E1	EN-14041
Resistance to staining	5 (group 1&2) - 4 group 3	EN-13329
Height difference between elements	Average <0.10mm Max <0.15mm	EN-13329
Openings between elements	Average <0.15mm Max <0.20mm	EN-13329

**Installation**

Installation	Refer to manufacturer guidelines	-
Warranty	30 year residential	-