



SOUND 12mm LAMINATE













| Fado Oak | Description | Test Standard |
|--------------------------------|--|----------------------|
| Country of origin | Poland | - |
| Dimensions | 1380 x 188 x 12mm | EN-13329 |
| Pack size | 1.30m² | - |
| Pallet quantity | 60 packs | - |
| Weight | 13.88kg | - |
| Construction | HDF 860kg/m³ | - |
| Classification | Class 23/33 | EN-13329 |
| Abrasion resistance | AC5 | EN-13329 |
| Bevel | 4V | - |
| Locking system | G5 Express Click | - |
| Structure | Cyncro 3D | - |
| Bathroom use | No | - |
| Underfloor heating | Yes | - |
| Warranty | 30 year residential | - |
| Technical Specification | | |
| Product | Description | Test Standard |
| Fire resistance | Cfl-s1 | EN-13501-1 |
| Impact resistance | Small ball - AC5 > 15N Big ball - AC5 > 1000mm | EN-13329 |
| Thermal resistance | 12mm: R<0.099 (m²K)/W | EN-12667 |
| Slip resistance | DS | EN-13893 |
| Formaldehyde emission | E1 | EN-14041 |
| Resistance to staining | 5 (group 1&2) - 4 group 3 | EN-13329 |
| Height difference | Average <0.10mm | EN-13329 |
| between elements | Max <0.15mm | |
| Openings between | Average <0.15mm | EN-13329 |
| elements | Max <0.20mm | |
| Installation | | |
| Installation | Refer to manufacturer guidelines | - |
| Warranty | 30 year residential | - |