



## X-TREME PLUS 10mm















| Castle Oak Silver              | Description                                    | <b>Test Standard</b> |
|--------------------------------|--|----------------------|
| Country of origin              | Germany  |                      |
| Dimensions                     | 1845 x 244 x 10mm                              | -                    |
| Pack size                      | 1.80m²   | -                    |
| Pallet quantity                | 42 packs                                       | -                    |
| Weight                         | -  | -                    |
| Construction                   | HDF  | -                    |
| Classification                 | Class 23/33                                    | -                    |
| Abrasion resistance            | AC5  | -                    |
| Bevel                          | 4V   | -                    |
| Locking system                 | G5 Express Click                               | -                    |
| Structure                      | Cyncro 3D                                      | -                    |
| Bathroom use                   | No   | -                    |
| Underfloor heating             | Yes  | -                    |
| Warranty                       | 30 year residential                            | -                    |
| <b>Technical Specification</b> |  |                      |
| Product                        | Description                                    | Test Standard        |
| Fire resistance                | Cfl-s1   | EN-13501-1           |
| Impact resistance              | Small ball - AC5 > 15N Big ball - AC5 > 1000mm | EN-13329             |
| Thermal resistance             | 10mm: R<0.075 (m²K)/W                          | -                    |
| Slip resistance                | -  | -                    |
| Formaldehyde emission          | <0.05 PPM                                      | EN-717-1             |
| Resistance to staining         | Grade 5  | EN-438-215           |
| Height difference              | Average <0.10mm                                | EN-13329             |
| between elements               | Max <0.15mm                                    |                      |
| Openings between               | Average <0.15mm                                | EN-13329             |
| elements                       | Max <0.20mm                                    |                      |
| Installation                   |  |                      |
| Installation                   | Refer to manufacturer guidelines               | -                    |
| Warranty                       | 30 year residential                            | -                    |