



Bearfoot

VISTA | ULTRA

Technical Data Information



Product Details	PO NO.:			
	Item Color:	Blackwing		
	Struction;	Multi-layer Engineered Wood Flooring -Herringbone		
	Specification:	18/4*90*450		
	Species:	European Oak	Plywood:	Eucalyptus mixed Poplar
	Grade :	ABCD	Moisture Content (MC):	6-8%
	Bevel:	0.5 for 4 side	Gloss:	About 5(AS SAMPLE)
	Filler:	Black filler	Surface finishment	Brush ,Penetrative Reactive stain , Uv Oil
	Glue Brand	Dynea	Lac Brand:	Treffert
	LOC System	Tongue and Groove	Installation:	Floating/Gluedown/Nail down
Maufacturing Process	<p>Selecting veneer and Prepare plywood material→Veneer Penetrate reactive →Drying and Balance(40℃-60℃)→Pressing→Repair knots→Fixed length and width→Sanding →Brush →Proflie(Tongue and groove)→Reactive stain on surface →Stain color and Coating→ Packaging</p>			
Technical Date(CE)	Essential Characteristics		Performance	Harmonised Technical Specification EN 14342: 2013
	Fire Reaction		Dfl-s1	
	Formaldehyde Emission according to EN 717-1:2005		E1	
	Content of PCP according to CEN/TR 14823:2004		PCP ≤5X10 ⁻⁶ n	
	Breakcage Resistance		NPD	
	Sliding		NPD	
	Thermal Conductivity		0.13W/mK	
Byological Durability		Class 1		
Certificates	CE,FSC,Floorscore,VOC,CARBIL...			